



SCM-10T
10W/4Ω



SCM-20T
20W/8Ω



SCM-30T
30W/12Ω



SCM-40T
40W/16Ω

- For Indoor & Outdoor applications such as in Halls, Auditorium, Airport Lounges.
- Weather resistant — for use under roof eaves. Foam layer to protect speakers from dust.
- Array of speakers radiate forward sound beam for wider audience coverage.
- Mounting clamps & hardware supplied.
- Column speakers in metal cabinet in light grey paint finish.
- Speaker connections through a terminal strip at the rear.
- Available in 100V line matching transformer and low impedance also.

SPECIFICATIONS

	SCM-10T	SCM-20T	SCM-30T	SCM-40T
Input Power	10W	20W	30W	40W
Power Taps	5/7.5/10W	5/10/20	10/20/30	10/20/40
Impedance	4Ω	8Ω	2Ω	16Ω
Frequency Response	150-10000Hz	150-10000Hz	150-10000Hz	150-10000Hz
Speakers	1 x (6"×4")	2 x (6"×4")	3 x (6"×4")	4 x (6"×4")
Dimensions (mm)	H240xW165xD145	H455xW165xD145	H390xW165xD145	H855xW165xD145
Weight	2.5Kg	4.2Kg	6.0Kg	7.4Kg